

SOILS

**THE TOUGHEST
PERFORMER**
« FOR YOUR FIELD »

60
SHUTTLEXL



3 CYLINDER DIESEL
ENGINE

12F+12R SYNCHROMESH
SHUTTLE TRANSMISSION

HEAVY LIFT
CAPACITY

EASY FRONT AND
LOADER ATTACHMENT

HEAVY DUTY
4WD



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

STRATEGIC
COLLABORATION
WITH
YANMAR

**THE TOUGHEST
PERFORMER**
« FOR YOUR FIELD »

60
SHUTTLEXL

SOLIS



FEATURES	60 SHUTTLEXL
ITL ENGINE	
No. of Cylinders / Capacity (cc) / Emissions Level	3/ 3065/ CRDI Stage V
After Treatment System	DOC + DPF
Rated Engine Power (kw/Hp)	43.2/58
Rated Engine Speed	2000
Max. Torque (Nm)	250@1400 Rpm
Aspiration	Turbo Charged
Intercooler	●
Air Cleaner	Dual Stage Dry Type
Block Heater	○
Updraft Exhaust Pipe	●
Downdraft Exhaust Pipe	○
Fuel Tank Capacity (L)	72
TRANSMISSION	
12x12 Synchro Shuttle Transmission (4WD)	●
Minimum Forward Speed	1.3kmph
Maximum Forward Speed	30kmph
12x12 Synchro Shuttle Transmission (4WD) with Creeper	○
Minimum Forward Speed	0.5kmph
Maximum Forward Speed	30kmph
FRONT AXLE	
2WD Front Axle	○
4WD Front Axle	●
Differential Lock	Mechanical
4WD Actuation	Mechanical
Brake Actuation	Mechanical Assist
PTO	
PTO Type	Mechanical
540/540E	●
540/1000	○
540/ground speed	○
HYDRAULIC	
Hydraulic Pump Flow (LPM)	45
Open Center Mechanical Draft Control	●
Top Link Draft Sensing	●
Liftomatic System	○
Lift Capacity	2500 KG
Linkage Category	II
Self Locking Linkages	○
Max. no. of Rear Remotes	2/3 (Opt.)
Max. no. of Mid Remotes	2
Mechanical Joystick Control for Mid Mounts with Valves	1 (Opt.)
REAR HITCHES	
E-Mark Swinging Drawbar	●

FEATURES	60 SHUTTLEXL
Cuna Type Ladder Hitch	○
Semi Automatic Ladder Hitch	○
Automatic Ladder Hitch	○
TRAILER BRAKES	
Without Trailer Brakes	●
Hydraulic Trailer Brakes	○
Dual Line Pneumatic Trailer Brakes	○
ELECTRICALS (ROPS/CAB)	
Battery	110AH 800CCA
Alternator	90A/120A
Button Operated Battery Cut off Switch, 3 Pinsocket, Seven on Trailer Socket	●
OPERATOR ENVIRONMENT	
Suspended platform (with ROPS)	●
Premium Driver Seat	○
Tiltable & Telescopic Steering	○
Integrated Loader Joystick	○
Cabin Air Conditioning (with Cabin)	○
DIMENSIONS (ROPS/CAB)	
Wheelbase (mm)	2225
Overall Height (mm)	ROPS: 2650 - 2700 CAB: 2450 - 2500
Overall Width (mm)	1825-1950
Overall Length (mm)	3830 - 4060
Front Track Width (mm)	1525 - 1570
Rear Track Width (mm)	1420 - 1440
Ground Clearance (mm)	310 - 355
Unladen Mass (Kg)	ROPS:2780 - 3315 CAB: 3340 - 3560
Tyre Combination	9.5x24 & 14.9x28
Optional Tyre Combinations	
Bias Tyres (2WD)	7.5x16 & 16.9x28
Bias Tyres (4WD)	9.5x24 & 16.9x28
Radial Tyres (4WD)	250/85 R24 & 420/85 R28
	280/85R24 AGRIMAX RT855 E 115A8/B SPL
	420/85R28 AGRIMAX RT855 E 139A8/B SPL
	320/70R24 AGRIMAX RT765 E 116D SPL
	480/70R28 AGRIMAX RT765 E 140D SPL
Industrial Tyres (4WD)	10-16.5 & 14.9-24
	12.5/80-18 & 18.4-24

● Standard ○ Optional

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

